




DPS-11

Door Status Contact

DPS-11 Ball Switch

The SDC DPS-11 ball switch is compatible with swinging or sliding doors. Recommended uses include communicated doors, mantraps, auto re-lock switches and high current applications.

- Contact:** SPDT, 5 Amps @ 30VDC
- Faceplate:** 2.75"H x 1.25"W x 0.125"D (69.85 x 31.75 x 3.18mm)
- Switch Depth:** 1.25" (31.75mm)
- Finish:** 628 Satin Aluminum



MC-4M

MC-4M Concealed Magnetic Contact

Designed for vandal resistance, the SDC MC-4M is installed in the mortise of a hollow metal or aluminum frame and wood, hollow metal or aluminum door.

- Contact:** SPDT, 50mA @ 30VDC
- Faceplate:** 4.875"H x 1.25"W x 0.125"D (123.83 x 31.75 x 3.18mm)
- Switch Depth:** 0.5" (12.7mm)
- Finish:** 628 Satin Aluminum



MC-4

MC-4 Magnetic Switch

Ideal for door status monitoring, the SDC MC-4 is easily installed in hollow metal and aluminum doors and frames.

- Contact:** SPDT, 50mA @ 30VDC
- Door/Frame Preparation:** 0.75" diameter x 1" deep (19.1 x 25.4mm)
- Gap:** 0.5" (12.7mm)

MC-7 High Security Magnetic Switch

Biased for high security door status monitoring, the MC-7 guards against false status indication caused by the presence of an additional magnet. Installed in hollow metal and aluminum doors and frames. Recommended for high security applications.

- Contact:** SPDT, 250mA @ 30VDC
- Door/Frame Preparation:** 1" diameter x 1" deep (25.4 x 25.4mm)
- Gap:** 0.5" (12.7mm)



MC-7