

CONTROL VALVES

TWO-POSITION POPTOP™ ZONE VALVES KZ SERIES



DESCRIPTION

The Kele KZ Series Two-Position PopTop™ zone valves offer a wide range of models to handle chilled water, hot water, and 15 psig (103 kPa) steam applications. PopTop valves feature removable actuators to aid in both installation and service. They are available in 2-way and 3-way body patterns and with normally open or normally closed actuators.

FEATURES

- Two- or three-way mixing/diverting body patterns
- Removable and replaceable actuator
- NPT, sweat, or inverted flare connections
- 2-position spring return control



KZG13A02A



KZG23B020



KZT2221




3

CONTROL VALVES





DIMENSIONS

in
(cm)



VALVE BODY SIZE	DIMENSIONS			
	A	B	C	D
1/2" Sweat	1-5/16 (3.33)	7/8 (2.22)	1-5/16 (3.33)	3-5/16 (8.41)
3/4" Sweat	1-3/8 (3.49)	7/8 (2.22)	1-11/16 (4.29)	3-3/8 (8.57)
1" Sweat	1-11/16 (4.29)	7/8 (2.22)	1-11/16 (4.29)	3-5/8 (9.21)
1/2" NPT	1-3/8 (3.49)	7/8 (2.22)	1-5/16 (3.33)	3-3/8 (8.57)
3/4" NPT	1-11/16 (4.29)	7/8 (2.22)	1-7/16 (3.65)	3-5/8 (9.21)
1" NPT	1-7/8 (4.76)	1 (2.54)	1-3/4 (4.45)	3-7/8 (9.84)
Inverted flare union	1-3/8 (3.49)	7/8 (2.22)	1-5/16 (3.33)	4-1/8 (10.48)
ACTUATOR	E	F	G	H
AG	2-3/8 (6.03)	3-11/16 (9.36)	2-3/8 (6.03)	1-1/4 (3.18)
AH	2-5/8 (6.67)	3-7/8 (9.84)	2-3/8 (6.03)	1-1/4 (3.18)



PIPING



WIRING





CONTROL VALVES

TWO-POSITION POPTOP™ ZONE VALVES KZ SERIES

3

CONTROL VALVES

SPECIFICATIONS

Size	1/2", 3/4", 1"
Cv Range	1.0 to 8.0
Connections	FNPT, Sweat, or inverted flare (3/4" only)
Flow Characteristic	Quick Opening
Leakage Rating	ANSI Class IV (0.01% of rated capacity)

Cv	General Operation	High Performance
	psid (kPa)	psid (kPa)
1-1.5	60 (414)	75 (517)
2.5-3	40 (276)	50 (345)
3.5-4	25 (172)	30 (207)
5	20 (137)	25 (172)
7.5-8	17 (117)	20 (137)

Maximum Pressure Rating	300 psig (2067 kPa)
Materials Of Construction	Brass valve body and seat, nickel-plated stem, BUNA N paddle; stainless steel base plate and aluminum cover on actuator
Media Compatibility	Hot or chilled water; 50% or less ethylene glycol; 15 psig steam
Media Temperature Range	32° to 200°F (0° to 93°C) with KZG actuator; up to 250°F (121°C) with KZH actuator
Supply Voltage	24 VAC ±10%; 120 VAC ±10%, 50/60 Hz; 208-277V models also available
Supply VA	7 VA

Supply Watts	6.5 W
Control Signal	Two-position, two-wire 18" (45.2 cm) leads
Wiring Action	Two-way valves: N.O./N.C. determined by choice of actuator; three-way valves: N.C. actuator only
Actuator Compatibility	KZG (general purpose) general closeoff (GCO) or KZH (high performance) high closeoff (HCO) type actuators only Poptop®
Actuator Mounting	N.O. contacts, 24-240 VAC, 101mA min to 5A max; 9-30 VDC @ 100 mA max
Auxiliary Contacts	Models with auxiliary switch available
Auxiliary Switch Drive Time	25 seconds maximum @ 60 Hz
Manual Override	N.C. actuators only
Operating Temperature	KZG actuator: maximum ambient 104°F (40°C); KZH actuator: maximum ambient 169°F (77°C)
Spring Return Time	9 seconds maximum
Weight	Valve bodies: <1.4 lb (.64 Kg) Actuators: 1.0 lb (.45 Kg)
Approvals	UL and ULc Listed; CE
Warranty	2 years

ORDERING INFORMATION

VALVE			
MODEL	DESCRIPTION		
KZ	Two-position PopTop electric valve		
TEMPERATURE			
T	Water		
S	Steam (must use high temperature actuator)		
CONFIGURATION			
2	Two-way		
3	Three-way		
CV SIZE			
2	1/2"		
3	3/4"		
4	1"		
CONNECTION			
1	Sweat - 1/2", 3/4", 1"		
2	NPT - 1/2", 3/4", 1"		
4	Inverted flare - 3/4" only		
CV CAPACITY			
	2-way	3-way	Size
1	1.0	1.5	1/2"
2	2.5	3.0	1/2", 3/4"
3	3.5	4.0	1/2", 3/4"
5	5.0	5.0	3/4", 1"
7	7.5	7.5	3/4"
7	8.0	8.0	1"

Note: Valve and actuator shipped separately.

*Inverted flare fittings not included with valve. They are field-supplied.

ACTUATOR	
MODEL	DESCRIPTION
KZ	VT Series actuator
CLOSEOFF	
G	General operation
H	High performance
VALVE OPERATION	
1	Normally closed*
2	Normally open**
TEMPERATURE	
3	Normal
4	Steam
VOLTAGE	
A	24 VAC, 50/60 Hz
B	120 VAC, 50/60 Hz
D	208 VAC, 60 Hz
T	277 VAC, 60 Hz
U	230/220 VAC, 50 Hz
LEADS	
02	18" Leads
OPTIONS	
0	None
A	End switch

* Three-way valves use N.C. actuator only; reverse ports for N.O.
** No manual override

STAG
680-243-6

RELATED PRODUCTS
Stainless steel tag on bead chain, 1" x 2" dogtag, custom engraved per order
Changeover thermostat with conduit fitting

30-158-A
30-158-B
30-158-D
30-158-T
30-158-U
436-252

ACCESSORIES
KZG/KZH Series actuator replacement motor, 24 VAC
KZG/KZH Series actuator replacement motor, 110/120 VAC
KZG/KZH Series actuator replacement motor, 208 VAC
KZG/KZH Series actuator replacement motor, 277 VAC
KZG/KZH Series actuator replacement motor, 230/240 VAC
3/4" flare-to-sweat fitting