



Verify flow rate anywhere, anytime.



DXN Portable Clamp-On Ultrasonic Flow Meter

Troubleshoot Flow Performance

Designed for systems engineers to quickly troubleshoot problems and verify performance during system commissioning and diagnostics, the Dynasonics® DXN portable clamp-on ultrasonic meter by Badger Meter is the perfect tool for any jobsite. Easy to install by clamping onto the outside of the pipe, the DXN measures flow using non-invasive ultrasonic sensors. Its portability makes it an excellent choice for measuring flows throughout the plumbing infrastructure to verify sensor, pump and valve performance.

With rapid response times, hybrid transit time and Doppler modes, the DXN captures more than 50 flow readings per second. Measurements are retained to memory stored in user-defined files and USB connectivity is included for easy downloads. With the only seven-inch, full-color advanced touchscreen interface in the industry, full-color graphing and wizard-based start-up configuration, the DXN is an excellent choice for easy programming and readability. Technicians can store site parameters using plain text and recall settings when they return for maintenance and diagnostic work in just a few touches. The compact design fits the meter and accessories into one convenient over-the-shoulder bag for easy portability. Applications include clean, solids-bearing or aerated liquids in closed full pipes 1/2 inch (12 mm) and larger.

Energy Monitoring

In addition to measuring liquid flow rate, the DXN is ideal for calculating hydronic energy usage. The built-in hydronic energy calculator makes it easy to facilitate energy studies on heating and cooling loops in building automation systems or in process applications. The DXN is equipped with heat flow capabilities designed to measure the rate and quantity of heat delivered or removed from devices such as heat exchangers. The DXN measures the volumetric flow rate of the heat exchanger liquid, the temperature at the inlet pipe and the temperature at the outlet pipe. Heat flow measurement can be delivered in Btu, Watts, Joules, Kilowatts, and others.

Applications

- Water
- Wastewater
- HVAC/Energy Monitoring
- Power Generation
- Mining
- Semiconductor
- Food and Beverage
- Flow System Commissioning and Troubleshooting




Features at a Glance

Measurement

- Switches automatically between transit time and Doppler measurement modes, as needed, to select the best measurement technique for the fluid
- Delivers accuracy up to ± 1 percent with a data sampling rate exceeding 50 flow readings per second
- Measures pipe thickness with optional gauge attachment to ensure accurate flow measurement

Operation

- Provides a customizable meter display screen to monitor up to four parameters
- Comes with a full keyboard on-screen control for easy data input
- Handles rigorous environments with an outdoor-readable, full-color display, glove-friendly touchscreen and robust protective cover



Data

- Stores user-customizable, site-specific parameters and captures data logs for measurement analysis
- Contains 1 GB of internal memory for data logging plus supports USB connectivity for additional storage capacity
- Downloads data easily to a PC via USB connectivity and provides a CSV file easily opened with Microsoft® Excel
- Supports multiple languages including English, Spanish, Portuguese, German, French, Italian, Dutch, Swedish, Norwegian, Russian, and Japanese
- Offers Modbus TCP/IP connectivity

Complete Portable Liquid Measurement Solution

Kit Selection

Scalable from a basic model to a full kit, the DXN delivers unprecedented levels of cost-effective, rugged and portable ultrasonic flow measurement. The basic model supports transit time measurement for pipe sizes up to 24 inches (609.6 mm) which is ideal for clean liquids and municipal wastewater applications. The full kit includes a hydronic energy calculator, pipe thickness gauge and has the ability to measure using Doppler technology making it suitable for liquids containing particulates and aeration for pipe diameters up to 120 inches (3048 mm). Five kits are available ranging from basic to full and each can be upgraded to meet changing system needs.

Kit Options

KIT	TRANSIT TIME TRANSDUCERS			DOPPLER TRANSDUCERS	NON-INVASIVE RTDS	WALL THICKNESS GAUGE	
	SMALL PIPE	STANDARD PIPE	LARGE PIPE				
Basic	✓	✓					Cables, power cord and carrying case
All Transit Time	✓	✓	✓				
Hybrid	✓	✓		✓			
Energy	✓	✓			✓		
Full	✓	✓	✓	✓	✓	✓	



Trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2013 Badger Meter, Inc. All rights reserved.

www.badgermeter.com

The Americas | Badger Meter | 4545 West Brown Deer Rd | PO Box 245036 | Milwaukee, WI 53224-9536 | 800-876-3837 | 414-355-0400
México | Badger Meter de las Americas, S.A. de C.V. | Pedro Luis Ogazón N°32 | Esq. Angelina N°24 | Colonia Guadalupe Inn | CP 01050 | México, DF | México | +52-55-5662-0882
Europe, Middle East and Africa | Badger Meter Europa GmbH | Nurtinger Str 76 | 72639 Neuffen | Germany | +49-7025-9208-0
Czech Republic | Badger Meter Czech Republic s.r.o. | Maříkova 2082/26 | 621 00 Brno, Czech Republic | +420-5-41420411
Slovakia | Badger Meter Slovakia s.r.o. | Racianska 109/B | 831 02 Bratislava, Slovakia | +421-2-44 63 83 01
Asia Pacific | Badger Meter | 80 Marine Parade Rd | 21-04 Parkway Parade | Singapore 449269 | +65-63464836
China | Badger Meter | 7-1202 | 99 Hangzhong Road | Minhang District | Shanghai | China 201101 | +86-21-5763 5412
 HYB-BR-00087-EN-02 (July 2013)