



## Refrigerant Detector for Occupied Spaces MVR-300™

### FEATURES

Fits in standard electrical boxes

Low profile/Flush mount

Two relays and Modbus Communications

Alarm options including: LED, buzzer, two levels, configurable delay and fail-safe

Refrigerant specific sensor

Self diagnostics and simple field calibration

Unique plug-in field replaceable pre-calibrated sensor

### BENEFITS

Easy to install

Aesthetically non-intrusive appearance

Notify building management & initiate counter measures

Alert occupants and remotely inform building management of alarm location for rapid response as required

Enhances safety<sup>1</sup> and minimizes refrigerant loss

Easy to maintain

Low cost of ownership

### DESCRIPTION

The MVR-300 detector is specifically designed to provide continuous monitoring for refrigerants associated with high-efficiency, high volume refrigerant cooling and heating systems, such as VRF/VRV (Variable Refrigerant Flow/Variable Refrigerant Volume) systems. Typical applications include hotels, dormitories, hospitals, office buildings, and apartment buildings.

The MVR-300 audible and visual alarms alert occupants and simultaneously communicate to Building Management Systems/Building Automation Systems (BMS/BAS). Two on-board relays can be used to close valves, activate alarm devices and exhaust fans or initiate emergency calls to rescue teams.

The on-board Modbus RTU interface provides real-time information about refrigerant concentrations, status and settings. It also enables custom configuration of the MVR-300 to any application specific requirements using multiple Modbus registers.

The MVR-300 is designed for easy installation and simple maintenance.

**<sup>1</sup>Important Note:** Large refrigerant leaks into occupied spaces can reach concentrations that pose a suffocation risk to the occupants. The MVR-300 is not designed to be used as the sole safety device for this risk. Safety of the occupants also must take a system designed approach that includes things such as ventilation, detection, early warning, mitigation and design redundancy.



ALARM AND SYSTEM STATUS LED

#### HOW TO CONTACT US:

Bacharach US Customer Service: +1 724 334 5000

Bacharach EU Customer Service: +353 1 284 6388

[www.mybacharach.com](http://www.mybacharach.com)

MVR-300 is a trademark of Bacharach, Inc.

[mybacharach.com](http://mybacharach.com)

For more information  
about the MVR-300 and  
other Bacharach products  
scan here.





COMMERCIAL



REFRIGERATION

## ORDERING INFORMATION

REFRIGERANT	P/N	LOW ALARM*	HIGH ALARM*	RANGE
R-410a	6203-0001	500 ppm	2,000 ppm	2,500 ppm
	6203-0002	1,000 ppm	2,000 ppm	5,000 ppm
	6203-0003	2,000 ppm	4,000 ppm	10,000 ppm
R-407c	6203-0011	500 ppm	2,000 ppm	2,500 ppm
	6203-0012	1,000 ppm	2,000 ppm	5,000 ppm
	6203-0013	2,000 ppm	4,000 ppm	10,000 ppm
R-404a	6203-0021	500 ppm	2,000 ppm	2,500 ppm
	6203-0022	1,000 ppm	2,000 ppm	5,000 ppm
	6203-0023	2,000 ppm	4,000 ppm	10,000 ppm
R-32	6203-0041	500 ppm	2,000 ppm	2,500 ppm
	6203-0042	1,000 ppm	2,000 ppm	5,000 ppm
	6203-0043	2,000 ppm	4,000 ppm	10,000 ppm

\*Factory default; can be changed through Modbus. Recommended 6 month testing/recalibration

## TECHNICAL DATA

PRODUCTS ATTRIBUTES	DESCRIPTION
<b>Detectable Gases</b>	R-410a, R-407c, R-404a, R-32
<b>Measuring Ranges</b>	2,500 ppm, 5,000 ppm, 10,000 ppm
<b>Housing</b>	Flush mount, white ABS, Fits in most 2-gang electrical back-boxes
<b>Size (L x W x D, approx.)</b>	6" x 4.1" x 1.75" (150 x 105 x 45 mm) including bezel
<b>Protection</b>	Indoor: IP40, NEMA 1
<b>Weight (approx.)</b>	8 oz (230 g)
<b>Power</b>	100 to 240 VAC, 50/60 Hz, 4 W max.
<b>Indicator</b>	Tri-color LED: green, amber, red
<b>Buzzer</b>	80 dB at 12" (30 cm)
<b>Relay</b>	Two SPDT: low alarm and high alarm / fault, normal or fail-safe; configurable
<b>Alarm Delay</b>	0 to 15 minutes; configurable 0, 5, 10, 15
<b>Wiring</b>	Power: 3-core cable, 14 to 20 AWG (0.5 to 2.0 mm <sup>2</sup> ) Relay: 3-core cable, 18 to 20 AWG (0.5 to 1.0 mm <sup>2</sup> ) Modbus: 2-core twisted pair shielded cable 18 to 24 AWG
<b>Modbus RTU</b>	Baud Rate: 9,600 or 19,200; configurable
<b>Environmental Conditions</b>	Operating Temperature: 32 to 120 °F (0 to 50 °C) Storage Temperature: 5 to 100 °F (-20 to 40 °C) Humidity: 5 to 90% RH, non-condensing Pressure: 23.6 to 32.5 inch of Hg (800 to 1,100 hPa)
<b>Elevation</b>	0 to 6,560 ft. (2,000 m) altitude
<b>Sensor life</b>	2 year minimum life with recommended 6 month testing and/or recalibration
<b>Approvals</b>	CE, UL/CSA/IEC/EN 61010-1

