

HAZARDOUS LOCATIONS

EXPLOSION CONDUIT ACCESSORIES GRT, EYM, PLG50 SERIES



CONDUIT OUTLET BOX GRT SERIES EXPLOSION PROOF OUTLET BOX

DESCRIPTION

These explosion proof, dust-ignition proof, cast-aluminum **conduit outlet boxes** are used with threaded metal conduit and are furnished with a cover and internal ground screw. They are suitable for Class I, Div 1 and 2, Groups B,C,D; Class II, Div 1 and 2, Groups E,F,G; and Class III, Div 1 and 2. In Class I, Group B atmospheres, all conduit runs must have a sealing fitting field installed adjacent to the enclosure. The UL File # is E10444.



ORDERING INFORMATION

MODEL	CONDUIT SIZE	COVER OPENING	CONSTRUCTION	WEIGHT lb (kg)
GRT50-A	3-1/2" NPT	3.38"	Cast Aluminum	1.4 (0.6)
GRT75-A	3-3/4" NPT	3.38"	Cast Aluminum	1.4 (0.6)



CONDUIT SEALING FITTING EYM SERIES

DESCRIPTION

These explosion proof, dust-ignition proof, malleable iron **conduit sealing fittings** are used with threaded metal conduit in horizontal or vertical applications. Fittings have female connections with one removable male nipple. They are suitable for Class I, Div 1 and 2, Groups A,B,C,D; Class II, Div 1 and 2, Groups E,F,G; Class III, Div 1 and 2. The UL File # is E10444.



ORDERING INFORMATION

MODEL	SIZE	TURNING RADIUS	KWIKO® CEMENT REQUIRED	CONSTRUCTION	WEIGHT lb (kg)
EYM-50	1/2"	1.06"	1 oz	Malleable Iron	0.8 (0.4)
EYM-75	3/4"	1.19"	2 oz	Malleable Iron	1.1 (0.5)
EYM-100	1"	1.38"	4 oz	Malleable Iron	1.5 (0.7)



CLOSE-UP PLUGS PLG50 SERIES

DESCRIPTION

These explosion proof, dust-ignition proof, steel **close-up plugs** are used with threaded metal conduit. They are suitable for Class I, Div 1 and 2, Groups A,B,C,D; Class II, Div 1 and 2, Groups E,F,G; and Class III, Div 1 and 2.



ORDERING INFORMATION

MODEL	SIZE	CONSTRUCTION	WEIGHT lb (kg)
PLG50R	1/2"	Steel, Recessed Head	0.1 (0.05)
PLG75R	3/4"	Steel, Recessed Head	0.1 (0.05)
PLG100R	1"	Steel, Recessed Head	0.2 (0.1)



8

HAZARDOUS LOCATIONS