

HAZARDOUS LOCATIONS

EXPLOSION PROOF CONDUIT ACCESSORIES AC1A, ACK6F, F01, AC1F01A



8

HAZARDOUS LOCATIONS



KWIKO® SEALING CEMENT MODEL AC1A

When mixed with water, according to label directions, **Kwiko Sealing Cement** forms a pourable cement for conduit sealing fittings.



ORDERING INFORMATION

MODEL	DESCRIPTION
AC1A	1 lb (0.5kg), 23 cu in (377.0 cu cm) volume when set

KWIKO® TWINPAK SEALING CEMENT MODEL ACK6F

Each plastic pouch in the **Kwiko® Twinpak** contains premeasured Kwiko® cement and premeasured water (in an inner bag). Squeeze the pouch to break the inner water bag, knead the mixture thoroughly and pour. The **Kwiko® Twinpak** includes an adequate amount of fiber filler packed separately.



ORDERING INFORMATION

MODEL	DESCRIPTION
ACK6F	Cement: 1.9 lb * (850g) Fiber: 0.3 lb (0.14kg), 25 cu in (410 cu cm) volume when set * Consists of five 6 oz (187g) cement pouches

Fiber Filler is used to prevent cement from leaking while it is in the fluid state.



ORDERING INFORMATION

MODEL	DESCRIPTION
F01	Quantity: 0.06 lb (0.03kg)

KWIKO® SEALING CEMENT AND FIBER FILLER KITS MODEL AC1F01A

The **Model AC1F01A** combines Model AC1A cement and Model F01 filler in a handy kit.



ORDERING INFORMATION

MODEL	DESCRIPTION
AC1F01A	Cement: 1 lb (0.5kg) Fiber: 0.06 lb (0.03kg), 23 cu in (377.0 cu cm) volume when set