



## MLS Series Multi-level Switch Product Selection Guide

---

This series of multi-level switch is custom made to application. Please call Kele sales representative at 877-826-9045 and use this guide to specify the requirements for quote.

Pressure, psig: \_\_\_\_\_

Temperature: \_\_\_\_\_

Media: \_\_\_\_\_

Mounting Configuration: **TOP**

- 1. Series:** **MLS**
- 2. Mounting Type:** 1/8" NPT  
1/4" NPT  
3/8" NPT  
1/2" NPT  
1" NPT  
1 1/4" NPT

- 3. Stem & Mounting Material:** Brass  
316SS

- 4. Float Materials:** 316SS  
Buna N

- 5. Wiring Type:** SPST Group 1 (Common)  
SPST Group 2 (Independent)



## MLS Series Multi-level Switch Product Selection Guide

---

**6. Switch Rating:** 50 VA SPST

**7. Lead Wires:** 24"

**Note:** Lead wire length is 24" if not specified

Cable- Optional

**8. Switch Actuation Level:**

Actuation Level	Distance to Actuation Level (in Inches*)	SPST Switch Operation**	
		Normally Open	Normally Closed
L6	_____		
L5	_____		
L4	_____		
L3	_____		
L2	_____		
***L1	_____		
****LO	_____		

---

\*Measured from bottom of the mounting plug or flange.

\*\*Switch position is "normal" with the unit dry (empty tank).

\*\*\*L1 is the distance to the lowest actuation level with mounting "up" and is the distance to the highest actuation level with mounting "down".

\*\*\*\*LO = Length overall, measured from the bottom of the mounting plug or flange to the end of the unit.

**9. J-Box Option:** Standard Pyromation Box

**10. Special Requirements:** Contact factory