



MLS500 Series Multi-level Switch Product Selection Guide

This series of multi-level switch is custom made to application. Please call Kele sales representative at 877-826-9045 and use this guide to specify the requirements for quote.

Pressure, psig: _____

Temperature: _____

Media: _____

Mounting Configuration: **TOP**

1. Series: **MLS500**

2. Mounting Type

- ½" NPT
- 1 ¼" NPT
- 2" NPT
- 3" 150# ANSI FLANG

3. Stem & Mounting Material:

- Brass
- 316SS

4. Float Materials:

- 316SS
- Buna N

5. Wiring Type:

- SPST Group 1 (Common)
- SPST Group 2 (Independent)

6. Switch Rating: 100 VA SPST



MLS500 Series Multi-level Switch Product Selection Guide

7. Lead Wires: 24"

Note: Lead wire length is 24" if not specified

Cable- Optional

8. Switch Actuation Level:

Actuation Level	Distance to Actuation Level (in Inches*)	SPST Switch Operation** (Check Type)	
		Normally Open	Normally Closed
L6	_____	_____	_____
L5	_____	_____	_____
L4	_____	_____	_____
L3	_____	_____	_____
L2	_____	_____	_____
***L1	_____	_____	_____
****LO	_____	_____	_____

*Measured from bottom of the mounting plug or flange.

**Switch position is "normal" with the unit dry (empty tank).

***L1 is the distance to the lowest actuation level with mounting "up" and is the distance to the highest actuation level with mounting "down".

****LO = Length overall, measured from the bottom of the mounting plug or flange to the end of the unit.

9. J-Box Option: Standard Pyromation Box

10. Special Requirements: Contact factory