



BAKA 4



Feed-through terminal
2 connections

Screw connection
22 x 6 x 23

Type	Cat. no.	mm	clear.	Qty.
BKA 4/1 BG	2158.2			100
BKA 4/1 BU	2158.5			100

IEC	UL	CSA
400	300	300
32	30	25
4 22-12		
6 3		
A3 V2		

0.2-4 -
0.2-4 0.2-4
0.2-4
9
0.5-1.0 Slotted M 3
-

PA 6.6 | -40 to +105°C
- | -

	Page	Qty.
EH 2 BG 2136.2	274	50
EH 15 BG 2945.2	275	50
EH 2/Z BG 2147.2	274	50

AQI 2/6/11 YE 2125.0	292	50
--------------------------------	-----	----

AQI 3/6/11 YE 2126.0	292	50
--------------------------------	-----	----

AQI 4/6/11 YE 2140.0	292	50
--------------------------------	-----	----

AQI 10/6/11 YE 2141.0	292	10
SDB 0.6x3.5 1086.0	422	1
PMC SD 6/50 WH 4702.7	340	500

BAKA 10



Direct mounting

Without labelling
Length Hole

Type	Cat. no.	mm	clear.	Qty.
BKA 4/2	2170.2	26.5	19.4	50
BKA 4/3	2171.2	32.6	25.5	50
BKA 4/4	2172.2	38.6	31.5	50
BKA 4/5	2173.2	44.8	37.7	50
BKA 4/6	2174.2	50.9	43.8	50
BKA 4/8	2175.2	63.1	56.0	20
BKA 4/10	2176.2	75.3	68.2	20
BKA 4/12	2177.2	87.4	80.3	20
BKA 4/13	2137.2	93.6	86.5	20
BKA 4/14	1036.2	99.7	92.6	20
BKA 4/15	2178.2	105.9	98.8	20
BKA 4/16	1037.2	111.8	104.7	20
BKA 4/18	1038.2	124.2	117.1	20
BKA 4/20	2179.2	136.2	129.1	10
BKA 4/24	1039.2	160.7	153.6	10



With one-sided label
Length Hole

Type	Cat. no.	mm	clear.	Qty.
BKA 4/2	2308.2	26.5	19.4	50
BKA 4/3	2309.2	32.6	25.5	50
BKA 4/4	2330.2	38.6	31.5	50
BKA 4/5	2331.2	44.8	37.7	50
BKA 4/6	2332.2	50.9	43.8	50
BKA 4/8	2333.2	63.1	56.0	20
BKA 4/10	2334.2	75.3	68.2	20
BKA 4/12	2335.2	87.4	80.3	20
BKA 4/13	2336.2	93.6	86.5	20
BKA 4/14	2337.2	99.7	92.6	20
BKA 4/15	2338.2	105.9	98.8	20
BKA 4/16	2339.2	111.8	104.7	20
BKA 4/18	2340.2	124.2	117.1	20
BKA 4/20	2341.2	136.2	129.1	10
BKA 4/24	2342.2	160.7	153.6	10

Length Hole

Type	Cat. no.	mm	clear.	Qty.
BKA 4/2	2343.2	26.5	19.4	50
BKA 4/3	2344.2	32.6	25.5	50
BKA 4/4	2345.2	38.6	31.5	50
BKA 4/5	2346.2	44.8	37.7	50
BKA 4/6	2347.2	50.9	43.8	50
BKA 4/8	2348.2	63.1	56.0	20
BKA 4/10	2349.2	75.3	68.2	20
BKA 4/12	2350.2	87.4	80.3	20
BKA 4/13	2351.2	93.6	86.5	20
BKA 4/14	2352.2	99.7	92.6	20
BKA 4/15	2353.2	105.9	98.8	20
BKA 4/16	2354.2	111.8	104.7	20
BKA 4/18	2355.2	124.2	117.1	20
BKA 4/20	2356.2	136.2	129.1	10
BKA 4/24	2357.2	160.7	153.6	10

BAKA 10



Feed-through terminal
2 connections

Screw connection
30 x 8 x 31

Type	Cat. no.	mm	clear.	Qty.
BKA 10/1 BG	1497.2			100
BKA 10/1 BU	1497.5			100

IEC	CSAus	CSA
400	300	300
57	57	57
10 22-8		
6 3		
A3 V2		

0.2-10 -
0.2-10 0.2-10
0.2-4
10
0.5-1.0 Slotted M 3
-

PA 6.6 | -40 to +105°C
- | -

	Page	Qty.
EH 3 BG 2939.2	275	20
EH 35 BG 2946.2	275	50

AQI 2/8/11 YE 2067.0	293	50
--------------------------------	-----	----

AQI 3/8/11 YE 2068.0	293	50
--------------------------------	-----	----

AQI 4/8/11 YE 2069.0	293	50
--------------------------------	-----	----

SDB 0.8x4.0 1087.0	422	1
PMC SB 8/40 WH 9323.7	342	400

BAKA 10



Direct mounting

Without labelling
Length Hole

Type	Cat. no.	mm	clear.	Qty.
BKA 10/2	1500.2	32.2	24.2	50
BKA 10/3	1501.2	40.3	32.3	20
BKA 10/4	1502.2	48.4	40.4	20
BKA 10/5	1503.2	56.5	48.5	20
BKA 10/6	1504.2	64.6	56.6	20
BKA 10/7	1505.2	72.7	64.7	20
BKA 10/8	1506.2	80.8	72.8	10
BKA 10/9	1507.2	88.9	80.9	10
BKA 10/10	1508.2	97.0	89.0	10
BKA 10/11	1509.2	105.1	97.1	10
BKA 10/12	1510.2	113.2	105.2	10