



### DESCRIPTION

The **K-332 PRV** station is a cartridge-style filter element that removes oil vapor, moisture, and dirt to one micron size. The **K-332-B** assembly includes a wall mounting bracket, filter cartridge, pressure reducing valve (PRV) and three shut-off/bypass valves for uninterrupted filter servicing. This complete airflow station is designed for airflow rates and pressure regulation up to 8 scfm and 30 psig (200 kPa). The regulator is adjustable up to 35 psig (241 kPa).



### ORDERING INFORMATION

MODEL	DESCRIPTION
<b>K-332</b>	PRV station with filters
<b>K-332-B</b>	PRV station with wall bracket, bypass and three isolating valves

### DESCRIPTION

The **Filtersoft FILN05** is a final-device pneumatic air filter with straight plastic barb fittings for 1/4" OD poly tubing. The **FILN05-B** model comes with 90° bent fittings. The microfibre disposable filter unit consists of a HEPA Microflex™ filter tube permanently bonded into a sealed nylon casting. As the filter shows signs of contamination, simply remove and replace. A replacement model **FILN05-R** is available without the barb fittings. **NOTE:** Not for use with synthetic lubricants.



FILN05

### SPECIFICATIONS

<b>Connections</b>	
<b>FILN05-B</b>	Plastic barbs, 90 degree, for 1/4" OD poly tubing
<b>FILN05</b>	Plastic barbs, straight, for 1/4" OD poly tubing
<b>FILN05-R</b>	Replacement filter, no barb fittings
<b>Air Capacity</b>	1.4 scfm, 1.5 psid
<b>Operating Temperature</b>	32° to 200°F (0° to 93°C)
<b>Maximum Pressure Rating</b>	100 psi (689 kPa) @ 100°F (38°C)
<b>Materials Of Construction</b>	Transparent nylon housing, HEPA Microflex™ filter
<b>Dimensions</b>	2.8"L x 1"DIA (7.0 x 2.5 cm)
<b>Weight</b>	0.3 oz (8.5 g)

### ORDERING INFORMATION

MODEL	DESCRIPTION
<b>FILN05</b>	In-line disposable air filter, straight, with barbs for 1/4" OD tubing
<b>FILN05-B</b>	In-line disposable air filter, 90° bent barbs for 1/4" OD tubing
<b>FILN05-R</b>	In-line disposable air filter, replacement, without barbs

### DESCRIPTION

The **Invensys TOOL-95-1** is a pneumatic controls calibration kit. It includes gauges, wrenches, tees, screwdrivers and a squeeze-bulb pump. The **TOOL-M-225** is a larger replacement squeeze bulb pump for higher air volumes.

### ORDERING INFORMATION

MODEL	DESCRIPTION
<b>TOOL-95-1</b>	Pneumatic thermostat calibration kit
<b>TOOL-M-225</b>	Large-capacity squeeze bulb pump

TOOL-95-1



TOOL-M-225