



PLUG-IN CLASS 2 TRANSFORMER

MODEL AM-24830A

DESCRIPTION

The **Model AM-24830A** is a UL listed plug-in Class 2 transformer. Simply plug it into any 120 VAC wall outlet and get a 24 VAC output with 20 VA of available power. Its small size and screw terminal output make it a convenient and portable source of low voltage for many applications.

FEATURES

- *Plugs into any 120 VAC wall outlet*
- *Convenient and portable source of low voltage*
- *Screw terminal output*
- *High efficiency, low heat generation*
- *UL listed*



SPECIFICATIONS			
Voltage input	120 VAC, 60 Hz, 30W from wall outlet	Insulation class	105°C minimum
Voltage output	24 VAC, 20 VA	Efficiency	70% at rated load
Input connections	Two bladed AC outlet plug (without ground)	Operating temp	14° to 104°F (-10° to 40°C)
Output connections	Screw terminals	Humidity	30% to 85%
Housing	Black plastic (not plenum rated)	Protection	Inherently current limited to meet Class 2
Dielectric strength	1.24 kV for one minute, input to output	Dimensions	3.2"H x 2.2"W x 1.9"D (8.1 x 5.6 x 4.8 cm)
		Approvals	UL listed, File #E112794, Class 2 Not Wet, Class 3 Wet

ORDERING INFORMATION

MODEL	DESCRIPTION
AM-24830A	Plug-in Class 2 Transformer, 120 VAC to 24 VAC, 20 VA