# **RELAYS & CONTACTORS**

PTF08A-E

### **OMRON RELAY SOCKETS P2RF. PF. PTF SERIES**



**OMRON** 

PTF11A

#### DESCRIPTION

The Omron PTF and PF Series of relay sockets are for use with the Omron LY / MK Series Relays. The P2RF is for use with the G2R-S relays. The PTF and PF Series include both blade and pin style sockets and are available for one, two, three, and four pole relays. The P2RF comes with a built-in relay hold down mechanism. All of these sockets can be DIN rail or surface mounted.

### **FEATURES**

• Use with Omron LY / MK / G2R-S relays

Socket Type

5-Pin, DIN rail or

Surface mount

8-Pin, DIN rail or

Surface mount

8-Pin, DIN rail or

Surface mount

11-Pin, DIN rail or

Surface mount

8-Pin, DIN rail or

Surface mount

11-Pin. DIN rail or

Surface mount

14-Pin, DIN rail or

Surface mount

- · Screw terminals with captive wire clamp
- Surface or DIN rail mount
- UL recognized, CSA certified and CE approved





Related

Relay

G2R-1

G2R-2

MK2

MK3

LY1, LY2

LY3

LY4

PTF14A-E

**SPECIFICATIONS** 

Model

P2RF-05-E

P2RF-08-E

**PF083A-E** 

**PF113A-E** 

PTF08A-E

PTF11A

PTF14A-E

Rated

Voltage

250V

250V

250V

250V

250V

250V

250V

Rated

Current

10A

5A

10A

10A

15A

10A

10A



PF113A-E

**Relay Hold Down** 

**Clip Accessory** 

N/A

(Built-In)

N/A

(Built-in)

PYC-A1

PYC-A1

PYC-A1

PYC-A1

PYC-A1



Up to two 12

AWG

Up to two 12

AWG



P2RF-08-E

| _ |                     |                      |   |  |
|---|---------------------|----------------------|---|--|
|   | Wire Size           | Weight               | Approvals   |  |
|   | Up to two 12<br>AWG | 0.13 lb<br>(0.06 Kg) | UL-recognized component,<br>File #E87929; CSA certified,<br>File #LR31928; CE certified |  |
|   | Up to two 12<br>AWG | 0.13 lb<br>(0.06 Kg) | UL-recognized component,<br>File #E87929; CSA certified,<br>File #LR31928; CE certified |  |
|   | Up to two 12<br>AWG | 0.13 lb<br>(0.06 Kg) | UL-recognized component,<br>File #E87929; CSA certified,<br>File #LR31928; CE certified |  |
|   | Up to two 12<br>AWG | 0.13 lb<br>(0.06 Kg) | UL-recognized component,<br>File #E87929; CSA certified,<br>File #LR31928; CE certified |  |
|   | Up to two 12<br>AWG | 0.11 lb<br>(0.05 Kg) | UL-recognized component,<br>File #E87929; CSA certified,<br>File #LR31928; CE certified |  |
|   |                     |                      | III recognized component  |  |

UL-recognized component,

1085

File #E87929; CSA certified,

File #LR31928; CE certified UL-recognized component,

File #E87929; CSA certified,

File #LR31928; CE certified

0.13 lb

(0.06 Kg)

0.17 lb

(0.08 Kg)

September 2016

kele.com 877-826-9037 USA

## **RELAYS & CONTACTORS**

Kele



OMRON RELAY SOCKETS P2RF, PF, PTF SERIES

