



GREYSTONE

ACCURACY BY DESIGN

FLEX-DUCT AVERAGE TEMPERATURE SENSOR TE200FD Series

The TE200FD flexible multi-point duct temperature sensor utilizes several precision sensors spaced at equal distances. The probe is FT6 plenum rated cable and is available in various lengths (see ordering chart). All probes are constructed to provide excellent heat transfer and a fast response. It is available with a variety of enclosures.



SPECIFICATION:


- Sensor Type:.....Thermistor or RTD
See Ordering Chart
- Temperature Range:..-20 to 60 °C (-4 to 140 °F)
Higher Ranges Available
Contact Greystone
- Wire Material:.....FT-6 Plenum rated cable
- Enclosure:.....Standard - ABS - UL94-V - NEMA 12 (IP64)
Round (E) - ABS - NEMA 12 (IP64)
Metal (M) - Gal. Steel - NEMA 1 (IP30)
Weatherproof (W) - Cast Alum. NEMA 3R (IP64)
- Termination:.....Pigtail 2 or 3 wire
Terminal block with (E) enclosure

TYPICAL INSTALLATION:

For complete installation and wiring details, please refer to the product installation instructions.

The Flex-duct average probes are installed through a hole in the side of the duct to monitor an average temperature within the duct. Select a probe length that allows for criss-crossing the duct multiple times. Install the probes in a straight section of duct at a suitable distance downstream from any heating, cooling or humidification devices.

Each enclosure style provides mounting tabs for ease of installation.



Typical Installation

PART NUMBER SELECTED

PRODUCT SELECTION INFORMATION:

MODEL	Product Description
TE200FD	Mult-point Flex Duct Averaging Temperature Sensor

CODE	Enclosure (ABS enclosure is standard)
B	ABS enclosure
C	Aluminum weatherproof box
D	Metal utility box
E	Round ABS, w/gasketed cover


CODE	Sensor
2	PT100-100 Ω Plat. IEC 751, 385 Alpha, thin film
5	1801 Ω, NTC Thermistor, ±0.2 C
6	3000 Ω, NTC Thermistor, ±0.2 C
7	10,000 Ω, type 3, NTC Thermistor, ±0.2 C
8	2.252 KΩ, NTC Thermistor, ±0.2 C
9	100,000 Ω, NTC Thermistor, ±0.2 C
12	PT1000-1000 Ω Platinum, IEC 751, 385 Alpha, thin film
13	1000 Ω Nickel
14	10,000 Ω, type 3, NTC Thermistor, ±0.2 C c/w 11K shunt resistor
15	PT3000 PTC Platinum, ±0.2 C
20	20,000 Ω, NTC Thermistor, ±0.2 C
24	10,000 Ω, type 2, NTC Thermistor, ±0.2 C

CODE	Probe Length/Sensor quantity
A	1800 mm (6') (4 Sensors)
B	3600 mm (12') (4 Sensors)
C	6100 mm (20') (4 Sensors)
D	7300 mm (24') (9 Sensors)




TE200FD B 7 C

Greystone Energy Systems, Inc. reserves the right to make design modifications without prior notice.




Dimensions:






ABS Enclosure





Metal Enclosure (M)



Round ABS Enclosure (E)



Weatherproof Enclosure (W)



Greystone Energy Systems, Inc. reserves the right to make design modifications without prior notice.



GREYSTONE

ACCURACY BY DESIGN

Greystone Energy Systems, Inc.
150 English Drive, Moncton, NB
Canada E1E 4G7

(506) 853-3057 Fax: (506) 853-6014
North America: 1-800-561-5611
e-mail: mail@greystoneenergy.com
www.greystoneenergy.com

RoHS
COMPLIANT



Greystone Energy Systems Inc. is one of North America's largest ISO registered manufacturers of HVAC sensors and transducers for Building Automation Management Systems.

We have conscientiously established a worldwide reputation as an industry leader by maintaining leading-edge design technology, prompt technical support, and a commitment to on-time deliveries. We take pride in our Quality Management System which is ISO 9001 certified, assuring our customers of consistent product reliability.

GREYSTONE HAS AN ISO 9001 REGISTERED QUALITY SYSTEM