



Product Options & Accessories

OPTIONS:

- Add -LCD to end of model for units with display.

ACCESSORIES:

- A-201 - Rubber tubing, 3/16" ID, 9 ft length.
- A-202 - Rubber tubing, 3/16" ID, lengths to 50 ft, per ft.
- A-210 - Aluminum tubing, 1/4" OD, 5 ft length, 500 psi maximum pressure @ 200°F.
- A-220 - Flexible vinyl tubing, clear 3/16" ID x 5/16" OD, lengths to 500 ft, per ft, 45 psi maximum pressure @ 73°F.
- A-221 - Flexible vinyl tubing, clear 1/8" ID x 3/16" OD, lengths to 500 ft, per ft, 40 psi maximum pressure @ 165°F.
- A-222 - Flexible vinyl tubing, clear .240" ID x .375" OD, lengths to 500 ft, per ft, 35 psi maximum pressure @ 73°F.
- A-223 - Black polyethylene 1/8" ID 1/4" OD, 10 ft length, 200 psi maximum @ 140°F.
- A-301 - Static pressure tip, for 1/4" metal tubing connection. 4.9" x .5" x .2", .05 .lb
- A-302 - Static pressure tip, for 3/16" and 1/8" ID plastic or rubber tubing. 4.7" x .3" x .2", .05 .lb
- A-303 - Portable static pressure tip, for 3/16" ID rubber or plastic tubing with 3" insertion. 3.9" x 1.1" x .9", .10 .lb
- A-306-A - Outdoor static pressure sensor, provides average outdoor pressure signal for reference in building pressurization applications, includes sensor, 50 ft vinyl tubing, mounting bracket and hardware.
- A-307 - Static pressure fitting, for 1/4" metal tubing connection. .8" x 1.5" x .6", .05 .lb
- A-308 - Static pressure fitting, for 3/16" and 1/8" ID plastic or rubber tubing. .2" x 1.6" x .2", .05 .lb
- A-414 - 316 SS clean room pressure sensor. .9" x 2.2" x .4", .05 .lb
- A-417A - Stainless Steel Wall Plate with Static Pressure Pickup
- A-418A - Plastic Wall Mount Enclosure with Static Pressure Pickup
- A-419A - Steel Ceiling Plate with Static Pressure Pickup
- A-420A - Outside Air Pickup Port with EU Enclosure
- A-435 - Field upgradeable LCD.
- A-465 - Flush mount space pressure sensor. 9.0" x 4.8" x 1.0", .10 .lb
- A-480 - Plastic static pressure tip.
- A-481 - Installer kit includes two static tips and 7 ft (2.1 m) of PVC tubing.