


PREPACKAGED SWITCHES


SIB02S

Enclosed Switch 20 Amp, 3 Position Maintained, On/Off/On




SIB04S

Enclosed Switch 20 Amp, 2 Position Maintained, On/On, 3 Wires





SIB05S

Enclosed Switch 20 Amp, 2 Position Maintained, On/Off, 2 Wires



SIBLS

Enclosed Switch 5 Amp, 30 Vac/dc, 3 Position Maintained, On/Off/On with LED Indicator



Made in USA Meets "Buy American" of ARRA 2009

SIB02S-RD
SIB04S-RD
SIB05S-RD
SIBLS-RD
• Red housing

SPECIFICATIONS

Operating Temperature: -30 to 140° F

Humidity Range: 5 to 95% (noncondensing)

Dimensions: 1.700" x 2.800" x 1.500" (w/ .500" NPT Nipple)

Wires: 16", 600V Rated

Approvals: UL Listed, UL916, C-UL, CE, RoHS

Housing Rating: UL Accepted for Use in Plenum, NEMA 1

SIB02S, SIB04S, RIB05S

Switch Ratings:
20 Amp Resistive @ 277 Vac
1110 VA Pilot Duty @ 277 Vac
770 VA Pilot Duty @ 120 Vac
20 Amp Ballast @ 277 Vac
10 Amp Tungsten @ 120 Vac
2 HP @ 277 Vac
1 HP @ 120 Vac

SIBLS Switch Ratings:
5 Amp @ 30 Vac/dc

Notes:

- Switch position label can be custom printed according to your needs, simply consult factory
- Connection to Wht/Yel may be omitted if LED is not needed (SIBLS) *