



Main

| | |
|-----------------------|------------------------------|
| Product range | Legacy |
| Product type | Socket |
| Product compatibility | relay 750BXR relay 750BXH |
| Number of terminals | 8 |
| Switch function | DPDT |
| Contact composition | 2 NO + 2 NC |

Complementary

| | |
|------------------------------|--|
| Line Rated Current | 10 A 15 A |
| Rated voltage | 300 V 600 V |
| Contact terminal arrangement | Mixed |
| Connections - terminals | Output screw clamp terminalssolid Output screw clamp terminalsstranded |
| Tightening torque | Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw < 1 N.m Screw < 0.8 N.m |
| Fixing mode | By screw M3.5, M3.5 panel By screws, M3 panel |
| Shape of screw head | Combination roundhead |
| Net Weight | 1.41 oz (40 g) |
| Width | 1.57 in (40 mm) |
| Depth | 2.24 in (57 mm) |

Environment

| | |
|---|-----------------------------|
| Ambient air temperature for storage | -40...221 °F (-40...105 °C) |
| Ambient temperature range - operational | -40...131 °F (-40...55 °C) |
| Flame retardance | UL94-V0 |
| Product certifications | UL CSA CE RoHS |

Ordering and shipping details

| | |
|------|----------------|
| GTIN | 03606480277962 |
|------|----------------|

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Approximate Dimensions

