



## Main

Product range	Legacy
Product type	Socket
Product compatibility	relay 784XDX suppressor module 70-ASMM diode 70-ASMD signalling device 70-ASMLG suppressor module 70-ASMR
Number of terminals	14
Switch function	4PDT
Contact composition	4 NO + 4 NC

## Complementary

Line Rated Current	16 A
Rated voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Output screw clamp terminalsolid Output screw clamp terminalsstranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw 1 N.m
Fixing mode	By screw M3.5, M3.5 panel Clip-on 35 x 15 mm symmetrical DIN rail
Shape of screw head	Combination roundhead
Net Weight	2.19 oz (62 g)
Width	1.97 in (50 mm)
Depth	3.13 in (79.6 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

## Ordering and shipping details

GTIN	03606480278181
------	----------------

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Approximate Dimensions

