

Q-Series Room Relative Humidity and Relative Humidity & Temperature Sensors



Figure 1. Q-Series Room Relative Humidity and Relative Humidity & Temperature Sensor.



Figure 2. Q-Series Room Relative Humidity and Relative Humidity & Temperature Sensor.



Figure 3. QFA2001 Room Humidity Sensor with Two-Wire 4-20 mA Output.

Description

The Q-Series Room Relative Humidity and Relative Humidity & Temperature Sensors monitor and transmit changes in humidity and temperature to the building control systems. These units are especially suited for applications where precise, stable humidity sensing is required.

Several models are available: humidity only versions (with $\pm 5\%$ or $\pm 2\%$ accuracy) and humidity and temperature sensing versions (with $\pm 2\%$ accuracy).

Sensing models (with display or full-featured) are also available. The full-featured models offer a wide range of features and functionality that can be used with a variety of building control systems:

- Liquid Crystal Display (LCD):** A two-line alphanumeric LCD allows simultaneous display of room temperature and relative humidity in degrees Fahrenheit or Celsius.

NOTE: QFAxxx.Dxxx models will only display temperature in Fahrenheit degrees. QFAxxx.Fxxx models can display in Fahrenheit or Celsius degrees.
- Digital Temperature Setpoint Adjustment:** The sensor's keypad allows error-free digital temperature setpoint adjustments in 0.5°F (0.2°C) increments. Setpoint values momentarily display as adjustments are made. The setpoint uses a matching current or voltage output signal.
- Override Button:** Allows an occupant to change to an unoccupied control schedule during the unoccupied cycle for a pre-determined time period.

Specifications – Humidity Output

Measurement range	0 to 100% rh
Accuracy of 5% rated sensors @ 73°F	±5% rh for 0% ≤ rh <30% or 70% ≤ rh <95% ±3% rh for 30% ≤ rh <70%
Accuracy of 2% rated sensors @ 73°F	±2% 0% to 100% rh
Temperature effect	Less than 0.1% per degree C
Sensing element	Capacitive polymer sensing element
Output signal	4 to 20 mA or 0 to 10 Vdc, 0 to 100% linear, proportional
Polarity protection	None

Specifications–Temperature Output (for combination RH/T units only)

Temperature output range	32°F to 122°F (0°C to 50°C)
Time constant at 0 to 50°C and 10 to 80% rh	Approximately 20 seconds in moving air
Accuracy	±1.8°F (±1°C)
Temperature output signal	Active: 4 to 20 mA or 0 to 10 Vdc
Calibration adjustments	None
Temperature setpoint output range	63°F to 83°F (17°C to 28°C)
Temperature setpoint output signal:	Active: 4 to 20 mA or 0 to 10 Vdc

General Specifications

Operating conditions	
Relative humidity	0 to 100%
Temperature	32°F to 122°F (0°C to 50°C)
Installation	18 AWG cable length shared in conduit with other sensor wiring 750 ft (229 m) maximum
Connections	Screw terminals
Housing Dimensions	
QFA2001	4" H × 3-1/2" W × 1-2/5" D (85 mm × 90 mm × 36 mm)
All others	3-11/32" H × 2-1/2" W × 1-1/2" D (85 mm × 63 mm × 38 mm)
Power requirements: 0 to 10V outputs	20 to 30 Vdc, max. 25 mA
Power requirements: 4 to 20 mA outputs	20 to 30 Vdc, max. 25 mA + 20 mA * outputs QFAx001.x = max. 45 mA QFAx071.W/B/Dx = max. 65 mA QFAx071.Fx = max. 85 mA
Material Type	Polycarbonate plastic
CE and UL-listed	UL 873 standard for temperature indicating and regulating equipment

Ordering Information

Product Number	Room Sensor Description
QFA3000.BU	RH 2%, 0 to 10V Signal, Beige, Siemens Logo
QFA3000.WU	RH 2%, 0 to 10V Signal, White, Siemens Logo
QFA3000.DBU	RH 2%, 0 to 10V Signal, Display, Beige, Siemens Logo
QFA3000.DWU	RH 2%, 0 to 10V Signal, Display, White, Siemens Logo
QFA3000.WTU	RH 2%, 0 to 10V Signal, White, TALON Logo
QFA3001.BU	RH 2%, 4 to 20 mA Signal, Beige, Siemens Logo
QFA3001.WTU	RH 2%, 4 to 20 mA Signal, White, TALON Logo
QFA3001.WU	RH 2%, 4 to 20 mA Signal, White, Siemens Logo
QFA3060.BU	RHT 2%, 0 to 10V Signa, Beige, Siemens Logo
QFA3060.FBU	RHT 2%, 0 to 10V Signal, Display, Temp Setpoint, Override, Beige, Siemens Logo
QFA3060.FWTU	RHT 2%, 0 to 10V RH and Temp Signal, Display, Temp Setpoint, Override, White, TALON Logo
QFA3060.FWU	RHT 2%, 0 to 10V Signal, Display, Temp Setpoint, Override, White, Siemens Logo
QFA3060.WTU	RHT 2%, 0 to 10V RH and Temp Signal, White, TALON Logo
QFA3060.WU	RHT 2%, 0 to 10V Signal, White, Siemens Logo
QFA2001	RH 5%, 4 to 20 mA Signal, 2-Wire, Off White, Siemens Logo

Accessories	Description
544-480A	Occupancy Override Button, 25-pack (Beige)
544-480B	Occupancy Override Button, 25-pack (White)
544-481A	Setpoint Door, 25-pack (Beige)
544-481B	Setpoint Door, 25-pack (White)
544-482A	Blank Bezel, 25-pack (Beige)
544-482B	Blank Bezel, 25-pack (White)
544-484A	Blanking Override Button, 25-pack (Beige)
544-484B	Blanking Override Button, 25-pack (White)
544-782A	Single Adapter Base Kit (Beige)
544-782B	Single Adapter Base Kit (White)
544-783A	Double Adapter Base Kit (Beige)
544-783B	Double Adapter Base Kit (White)
544-784	Non-Conduit Rough-In Kit
544-785A	Extender Ring Kit (Beige)
544-785B	Extender Ring Kit (White)
AQF3051	Replaceable Sensing Element (2% versions only)
ARG70	Adapter plate to mount QFA2001 on a 2" x 4" electrical box

Information in this publication is based on current specifications. The company reserves the right to make changes in specifications and models as design improvements are introduced. TALON is a registered trademark of Siemens Industry, Inc. Other products or company names mentioned herein may be the trademarks of their respective owners.

© 2016 Siemens Industry, Inc.